



Gammapac panels are multipurpose panels designed to meet a wide range of applications. They are suitable for all coverings used with access flooring.

Composition

The **Gammapac** panel is made up as follows :

- A high density resin bonded core, thickness 30 mm or 38 mm.
- A bottom plate of 0.5 mm thick galvanized steel.
- An ABS surround, heat bonded to the edge of the core.

Coverings

The **Gammapac** panel is available with the following coverings :

- High pressure laminate
- Vinyl
- Linoleum
- Textile covering
- Rubber

Dimensions

Standard size : 600 mm.
Size 675 mm for thickness 38 mm.
Special sizes, on request.

Options

For panels without covering only :

- Top varnished.
- Top plate of 0.5 mm thick galvanized steel.

Fire classification

The **Gammapac** panel is classed M1 (SNPE report n° 13149-07).
The **Gammapac** panel, 38mm thick, is classed F30, according to DIN 4102.

Electrical resistance

It varies from 5×10^5 to 2×10^{12} Ohms, depending on the properties of the covering.

Acoustic

The acoustic insulation measured between 2 adjacent rooms, separated by a densely insulated partition, varies from 44 to 50 dBA, depending on the thickness of the panel and the covering (Dn,f,w according to Standard EN ISO 140-12).

Load classes

	Framework	Class	Certificate
Gammapac 30 without covering	Self-supporting	1A (or 1B or 2C)	Nr. 03.10.30.08
	Stringers 30/15	2A (or 3B or 4C)	Nr. 03.10.30.05
Gammapac 30 with HPL covering	Self-supporting	2A (or 2B or 3C)	Nr. 03.10.30.11
	Stringers 30/15	2A (or 3B or 4C)	Nr. 03.10.30.02
Gammapac 38	Self-supporting	2A (or 4B or 5C)	Nr. 03.07.10.06
	Stringers 30/15	4A (or 5B or 5C)	Nr. 03.07.10.08
	Stringers 45/15	5A (or 5B or 5C)	Nr. 03.07.10.10

NB : A system classed **2A** is a system for which the ultimate load is at least 6kN (load class 2).
The working load of this system is at least 3 kN, with a safety factor of 2, for a deflection less than 2.5 mm (deflection class A).

See tables below for the other classes.

Survey Institute : SOCOTEC CONSULTING.

Load classes according to NF EN 12825 and using safety factor = 2.0.

Load class	Class 1	Class 2	Class 3	Class 4	Class 5	Class 6
Ultimate load	>4kN	>6kN	>8kN	>9kN	>10kN	>12kN
Working load	>2kN	>3kN	>4kN	>4.5kN	>5kN	>6kN

Deflection class	Maximum deflection
A (the most stringent)	2.5 mm
B	3.0 mm
C (the least stringent)	4.0 mm

31bis, rue des Longs Prés - 92100 Boulogne - Billancourt

Tél. : 33 (0)1 41 23 10 10 - Fax : 33 (0)1 41 23 10 04

Pedestals



Standard pedestal



Pedestal low height



Pedestal great height

The pedestals are made up of :

- a square baseplate of galvanized steel.
- a steel galvanized column welded to the baseplate.
- a die-cast aluminium or steel head, according to the type of pedestal.
- a locking nut for height adjustment.

Standard pedestal

The head has a sufficient length to adjust the height + or - 20 mm. Ridges moulded on the head allow a positive location of the panels.

Pedestal for low finished height

The threaded steel head allows an adjustment of + or - 7 mm. The panels lay directly on a conductive pad. These pedestals allow a minimum finished height of 70 mm.

Pedestal for great finished height (more than 800 mm)

The column is a square hollow section of galvanized steel. The base, the head and the locking nut are the same as for the standard pedestal.

Installation

The pedestals are bonded to the concrete by way of a special adhesive, or may be mechanically fixed.

A device on the baseplate permits a quick and safe fixing of the copper earthing strap.

Stringers



Lockable stringer

Lockable stringers

They are made of galvanized steel . They are designed for location on pedestal heads.

The stringers provide rigidity to the understructure, and stability against lateral strain.

The depth of the section is adapted to the required performances :

- 30 mm deep : type 30/15.
- 45 mm deep : type 45/15.

Special stringers

When pedestals are omitted due to obstructions, i.e. electrical services, air ducting, etc., special bridging stringers may be used.

Within these particular areas, it is admitted that the deflection may be 20% more than for the rest of the raised floor.